

---

## TECHNICAL DATA SHEET PERMANENT ASPHALT REPAIR (PAR)

### DESCRIPTION

Our unique formulation is designed so that you can achieve optimum performance all year long in any weather conditions with one product

### BASIC USES

Permanently repairs any holes in asphalt or concrete, in all types of weather even wet/freezing or extreme heat conditions

### FEATURES

Unique formulation premixed and ready to use Permanent repair = Cost effectiveness Convenient packaging, for all repairs 23kg bags Easy 3-step repair

Backed by Cohe Group's strict quality control Testing at independent laboratories

### PREPARATION

Clean out any loose chunks or debris using a stiff broom or blower to achieve a sound surface to bond to.

### APPLICATION

Place PAR in hole, in layers of 75mm at a time. Compact PAR with a taper, roller or by driving over it. Repeat Until the hole is filled to the desired thickness. To speed set up time, reduce tacky surface, dust with sand Cement. READY TO DRIVE ON.

### Q&A

- |                    |  |
|--------------------|--|
| • Shelf life:      | 1 Year                                   |
| • Seasonal grades: | No- One purpose grade                    |
| • Setup time:      | Immediate                                |
| • Coverage:        | 23kg Bag covers 05sqm at a depth of 25mm |



#### TECHNICAL DATA

- Asphalt Content: ASTM D2172-92
- Static Stripping: ASTM D1664-80
- Kinetic Stripping: OPSS 1153-02-01

#### SAFETY

Please refer to SDS

#### WARRANTY DISCLAIMER

The information herein is to assist customers in determining whether our products are suit able for their application. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to the contents and suitability. We warrant our products to meet our written specifications. Nothing herein shall constitute a warranty expressed or implied, including any warranty of merchantability or fitness, nor is protection from any loss or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.